



INSTALLATION



SIDE-BY-SIDE SHOTGUN BELT GUARD 1542

FITS: '00-UP SOFTAIL (EX. '00-UP FXSTD, '06-UP FXST/B/C/S AND '07-UP FLSTF)

PARTS INCLUDED

- 1 Side-By-Side Shotgun Belt Guard
- 1 Hardware Kit, including:
 - 2 5/16-18 x 1 Button Socket Cap Screw (BSCS)
 - 4 5/16 Flat Washer
 - 2 5/16-18 Hex Nut
 - 1 Sleeve
 - 1 Grommet
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING! THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Set of hex wrenches, combination wrenches or socket set and ratchet

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

NOTE This product contains natural wood that requires special care. Periodically wipe the wood with linseed oil or some other type of wood care product.

PROCEDURE

STEP 1 Park the motorcycle on a hard, level surface; turn off the ignition.

STEP 2 Remove the acorn bolt, acorn nut, washer and bolt from the stock belt guard. This hardware will not be re-used.

-cont.-

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

For purchasing Kuryakyn products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Kuryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson or GL & Metric Cruisers.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA All Rights reserved.

PROOF-OF-PURCHASE



kuryakyn.com

STEP 3 Remove the stock belt guard; set it aside, it will not be re-used. See [PIC.1](#).

STEP 4 Place a 5/16 flat washer over two 5/16-18 x 1 BSCS.

STEP 5 Install the grommet and sleeve in the rear mounting tab of the Side-By-Side Shotgun Belt Guard. See [FIG.1](#).

STEP 6 Hold the Side-By-Side Shotgun Belt Guard in place; ensure that the front mounting tab is between the metal tab on the swingarm and the plastic bottom belt guard. See [PIC.2](#). The rear mounting tab will locate to the outside of the metal tab on the swingarm. See [FIG.1](#).

STEP 7 Align the holes in the mounting tabs of the belt guard and swingarm; insert the two screws and washers from Step 4 through the holes shown in [PIC.2](#).



STEP 8 Place a flat washer over the protruding ends of the screws from STEP 7. See [FIG.1](#).

STEP 9 Secure the Side-By-Side Shotgun Belt Guard with the two included hex nuts; align the belt guard and tighten nuts.

ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

WARNING! IMPROPER INSTALLATION OR USE OF THIS PRODUCT COULD RESULT IN SERIOUS INJURY OR DEATH.

CAUTION! Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.



THE REAR MOUNTING TAB LOCATES ON THE OUTSIDE

INSERT THE 5/16-18 SCREWS AND WASHERS

THE FRONT MOUNTING TAB MUST BE BETWEEN THE METAL TAB AND PLASTIC BELT GUARD

Ride On!