



LICENSE PLATE MARKER LIGHT MOUNT 4247

UNIVERSAL FIT; FITS MOST MODELS WITH LICENSE PLATE BRACKETS FOR 4" X 7" LICENSE PLATES.

PARTS INCLUDED

- Signal Plate A
- 1 Signal Plate B
- 1 Backing Plate
- 1 Hardware Kit, including:
- 4 1/4 20 x 3/4" BSCS Fastener, Stainless
- 4 1/4 20 Hex Nylon Lock Nut, Stainless
- 4 1/4" Flat Washer, Stainless
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

PLEASE NOTE

It is the installers' responsibility to make sure all fasteners (including pre-assembled) are tightened before operation of motorcycle. Küryakyn will not warranty components that are lost due to improper installation. Periodic maintenance may be required.

TOOLS SUGGESTED

Allen wrenches, 7/16" socket or wrench.

ATTENTION! A stock Harley-Davidson license plate mount is shown in the following procedure; your license plate mount may vary but the procedure is the same.

PROCEDURE

STEP 1 On the stock license plate bracket, loosen the top clamp fastener and remove your license plate. See <u>PIC.1</u>.

STEP 2 Place the backing plate over the license bracket and center the backing plate on the license plate bracket. Adjust the top clamp to fit the backing plate. Tighten the top clamp fastener.

-cont.-



CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com or call 715.247.2983

LIMITED WARRANTY

Küryakyn warrants that any Küryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Küryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- · The product must be properly installed, maintained and operated under normal conditions.
- Küryakyn makes no warranty, expressed or implied, with respect to any gold plated products.

 Küryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Küryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breech of contract or duty between Küryakyn and a customer.

> · Küryakyn products are often intended for use in specific applications. Küryakyn makes no warranty if a Küryakyn product is used in applications other than intended.

· Küryakyn electrical products are warranted for one
(1) year from the date of purchase by the consumer.
Components of Küryakyn products containing L.E.D.s
will be warranted for defects in materials and
workmanship for 3 years from the date of purchase.

Küryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Küryakyn. Küryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today–select the "CATALOGS" icon. Each Küryakyn product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Küryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Küryakyn USA All Rights reserved



STEP 3 Determine the orientation of the signal plates. You can mount the plates on either side of the license plate bracket, depending on whether you want the accessory light mounts on the top or on the bottom. See <u>PIC.2</u> and <u>PIC.3</u>. You can also mount the signal plates to face toward the front or rear of the bike.


Küryakyn

STEP 4 Place the signal plates behind the backing plate, then place your license plate over the backing plate. Secure the assembly with the provided fasteners See <u>PIC.4</u>.

STEP 5 Mount your accessory lights (not included) to the signal plates. Refer to your accessory lights installation instructions for specific information.

STEP 6 Check that all fasteners are secure before riding.

Ride On!







PAGE 2